

## Dehumidifier

### Home Dehumidifier



BKDH-820E/830E

#### Features:

- \* With active carbon filter. \* Timing range: 1~24 hours.
- \* LED display, indicate humidity. \* Microcomputer control, intelligent operation.
- \* With drains to keep continuous drainage function.
- \* Low temperature available, efficient automatic defrosting system.
- \* E series, high sensitivity causative touch screen, D series, button screen.
- \* Voice prompt function: the dehumidifier stop work and alarm when the water tank is full.

#### Technical Parameters:

| Model                     | BKDH-820E                                | BKDH-830E   |
|---------------------------|------------------------------------------|-------------|
| Humidity Removal Capacity | 20L/24H                                  | 30L/24H     |
| Humidity Adjusted Range   | 40%~90%RH                                |             |
| Air Circulation           | 280 m³/h                                 | 310 m³/h    |
| Refrigerant               | R134A                                    |             |
| Material                  | ABS                                      |             |
| Applying Area             | 30~70 m²                                 | 35~80 m²    |
| Power Supply              | Standard: 220V 50Hz, Optional: 110V 60Hz |             |
| Consumption               | 280W                                     | 330W        |
| Water Tank                | 5.1L                                     |             |
| External Size (W*D*H)     | 373*266*612mm                            |             |
| Packing Size (W*D*H)      | 410*310*680mm                            |             |
| Net Weight                | 14kg                                     | 14.5kg      |
| Gross Weight              | 15kg                                     | 15.5kg      |
| Border Color              | Green/Black                              | Green/Black |



BKDH-850D/860D

BKDH-860E

#### Features:

- \* With active carbon filter. \* Timing range: 1~24 hours.
- \* LED display, indicate humidity. \* Microcomputer control, intelligent operation.
- \* With drains to keep continuous drainage function.
- \* Low temperature available, efficient automatic defrosting system.
- \* E series, high sensitivity causative touch screen, D series, button screen.
- \* Voice prompt function: the dehumidifier stop work and alarm when the water tank is full.

#### Technical Parameters:

| Model                     | BKDH-850D                                | BKDH-860D | BKDH-860E   |
|---------------------------|------------------------------------------|-----------|-------------|
| Humidity Removal Capacity | 50L/24H                                  | 60L/24H   |             |
| Humidity Adjusted Range   | 40%~90%RH                                |           |             |
| Air Circulation           | 710 m³/h                                 | 723 m³/h  |             |
| Refrigerant               | R410A                                    |           |             |
| Material                  | ABS                                      |           |             |
| Applying Area             | 50~110 m²                                | 70~120 m² |             |
| Power Supply              | Standard: 220V 50Hz, Optional: 110V 60Hz |           |             |
| Consumption               | 700W                                     | 740W      |             |
| Water Tank                | 10L                                      |           |             |
| External Size (W*D*H)     | 436*290*720mm                            |           |             |
| Packing Size (W*D*H)      | 490*350*780mm                            |           |             |
| Net Weight                | 23.5kg                                   | 24.5kg    |             |
| Gross Weight              | 26kg                                     |           |             |
| Border Color              | Black                                    |           | Black/Green |